



Republic Brass Sales, Inc.
 619.229.8304
 6566 Federal Blvd
 Lemon Grove, CA 91945
 www.republicbrasssales.com

HIGH-TEMP HOSE HIGH PRESSURE MIL-H-24135/13

Specification: MIL-H-24135/13

Pressure Rating: 1250 - 5000 PSI

Sizes: 1/4" - 2"

Application: High pressure hydraulics, petroleum based fluids
 and fire resistant types

Operating Temperature Range: -40°F to +300°F

FITTING REFERENCE:
 MIL-F-24787

SAE 37°:
 4721-RBS

CPV:
 190909-RBS
 191304-RBS

FLANGE:
 FC9506-RBS
 FC9224-RBS

DOGLEG:
 191305-RBS



MIL-H-24135/13
 EQUAL TO AEROQUIP P/N AE373

CONSTRUCTION: ELASTOMER TUBE, DOUBLE WIRE BRAID REINFORCEMENT AND BLUE ELASTOMER COVER

RBS P/N	EQUAL TO AEROQUIP NUMBER	HOSE I.D.	WORKING PRESSURE	BURST PRESSURE	MIN. BEND RADIUS	WEIGHT/FT.
24135/13-4	AE373-4	1/4	5,000 PSI	20,000 PSI	4.00	0.31
24135/13-6	AE373-6	3/8	4,000 PSI	16,000 PSI	5.00	0.42
24135/13-8	AE373-8	1/2	3,500 PSI	14,000 PSI	7.00	0.51
24135/13-10	AE373-10	5/8	2,750 PSI	11,000 PSI	8.00	0.59
24135/13-12	AE373-12	3/4	2,250 PSI	9,000 PSI	9.50	0.75
24135/13-16	AE373-16	1	2,000 PSI	8,000 PSI	12.00	1.04
24135/13-20	AE373-20	1 1/4	1,625 PSI	6,500 PSI	16.50	1.68
24135/13-24	AE373-24	1 1/2	1,250 PSI	5,000 PSI	20.00	1.91
24135/13-32	AE373-32	2	1,125 PSI	4,500 PSI	25.00	2.39

